



**ELEVATION**

N.T.S.

**NOTES**

1. FENCE SECTION IS TYP.
2. ALL POST AND RAILS SHALL BE COATED BY FUSION BONDING. (ASTM 668 TYPE 2B). COLOR: WOODLAND GREEN OR BLACK (OR AS DIRECTED).
3. ALL ASSORTED HARDWARE SHALL BE OF A NON-RUSTING TYPE.
4. PIPE WEIGHTS:
  - 1 5/8" O.D. = 2.27 LBS./LIN. FT.
  - 2 1/2" O.D. = 3.65 LBS./LIN. FT.
  - 3" O.D. = 5.79 LBS./LIN. FT.
5. ALL FABRIC SHALL BE SECURED TO POSTS AND RAILS AT 24" MAX. SPACING.



**THE MARYLAND-NATIONAL CAPITAL PARK AND PLANNING COMMISSION**  
 Department of Park and Planning, Montgomery County, Maryland

PARK DEVELOPMENT DIVISION 9500 BRUNETT AVENUE SILVER SPRING, MD 20901	DATE APPROVED	<b>OUTFIELD CHAIN LINK FENCE</b> (10'-0" HIGH)	REVISED	DATE	STANDARD NO.
	CHIEF ENGINEER				<b>109</b>
	SUPERINTENDENT OF PARKS				