


**ELEVATION**  
N.T.S.

**NOTES:**

1. POSTS AND CROSSBARS SHALL BE 3.548" I.D. 4.000" O.D. GALVANIZED STEEL PIPE. FOR REMOVABLE POSTS OF THIS SIZE, USE 5.047" I.D. 5.563" O.D. MINIMUM GALVANIZED STEEL PIPE SLEEVES.
2. ALL PIPE JOINTS ARE TO BE WELDED.
3. ALL PIPE SHOULD BE ETCHED WITH ACID BEFORE PAINTING AND THEN PRIMED BEFORE APPLYING 2 COATS OF SEMI-GLOSS ALKYD ENAMEL PAINT, COLOR: WHITE.
4. OPTIONAL GOAL POST MAY BE USED IN FORM OF SINGLE STEEL POST SET BEHIND THE END ZONE IN A 30" DIA. X 4' - 0" MINIMUM CONCRETE BASE AND A CANTILEVERED HORIZONTAL CROSSBAR AND TWO UPRIGHTS OF THE SAME HEIGHT AND SPACING AS FOR DUAL SUPPORT POSTS.



**FOOTBALL GOAL**



The Maryland-National Capital Park and Planning Commission  
Montgomery County Department of Parks

Detail No.

**141**

04-06-07