



NOTES:

ELEVATION

N.T.S.

1. FENCE ELEVATION IS TYPICAL. ACTUAL LOCATION OF GATE SHALL BE AT THE EXACT PLACE AS SHOWN ON THE SITE PLAN.
2. NO CONCRETE SHALL BE PLACED IN FOOTING WITHOUT ONSITE INSPECTION AND APPROVAL OF THE COMMISSION CONSTRUCTION MANAGER.
3. ALL POSTS AND RAILS SHALL BE SCHEDULE 40, HOT-DIPPED GALV. ZINC WITH CHROMATE CONVERSION COATING AND FUSION BONDED VINYL, (ASTM 668 TYPE 2B) COLOR: WOODLAND GREEN OR BLACK (OR AS DIRECTED), SHALL MATCH FABRIC.
4. ALL ASSORTED HARDWARE SHALL BE FUSION BONDED VINYL.
5. PIPE WEIGHTS:
 - 1 5/8" O.D. = 1.83 LBS./LIN. FT.
 - 2 1/2" O.D. = 3.11 LBS./LIN. FT.
 - 3" O.D. = 4.64 LBS./LIN. FT.
6. FABRIC TO BE NO. 9 A.S.W. GA. GALV. STEEL CORE, 1 3/4" DIAMOND MESH, FUSION-BONDED (ASTM 668 TYP. 2B) COLOR: "WOODLAND GREEN" OR "BLACK" (OR AS DIRECTED)
7. ALL PAVEMENT SURFACES ARE TO BE COLOR COATED INCLUDING EDGES OUTSIDE THE FENCE.
8. FOR TENNIS COURT PAVEMENT SECTION, SEE STANDARD NO. 203



THE MARYLAND-NATIONAL CAPITAL PARK AND PLANNING COMMISSION
 Department of Park and Planning, Montgomery County, Maryland

PARK
 DEVELOPMENT
 DIVISION
 9500 BRUNETT AVENUE
 SILVER SPRING, MD 20901

DATE APPROVED _____
 CHIEF ENGINEER _____
 SUPERINTENDENT OF PARKS _____

CHAIN LINK FENCE
 (10'-0" HIGH)

REVISED	DATE

STANDARD NO.

206